

Amendments to the Specification

Please replace the paragraph beginning page 2, line 16, with the following amended paragraph:

--To achieve these objects of the present invention, the grip strip fabrication method comprises the steps of: (a) preparing a substrate sheet made from a ~~first~~ first material, the substrate sheet having a plurality of through holes through top and bottom sides thereof, the first material being a polymer; (b) dipping or coating the substrate sheet with a melt second material such that the through holes of said substrate sheet are filled up and at least one of the top and bottom sides of the substrate sheet is covered by the second material, the second material being a polymer different from the first material; and (c) hardening the second material-covered substrate sheet.--

Please replace the paragraph beginning page 3, line 26, bridging page 4, with the following amended paragraph:

--(a) As illustrated in FIG. 2, a meshed net member 10 formed of interwoven warp threads 12 and ~~west~~ weft threads 14 is firstly prepared. The warp threads 12 and the ~~west~~ weft threads 14 can be obtained from natural fibers, synthetic fibers, polymers, or metal. According to the present embodiment, the meshes 16 of the meshed net member 10 are

Appln. No. 10/725,406  
Amendment dated August 30, 2005  
Reply to Office Action of June 2, 2005

orderly arranged in an array, having a rectangular shape of  
size about 5x4mm.--